

NETUM NT-W3 CCD Wired Barcode Scanner

?????????: ??? ?????????? ?????

????

???? ??????? 37,96 €

???????



Κατόπιν παραγγελίας
έως 30 ημέρες
Παράλαβή από κατάστημα
Παρόδοση e-Shop

[????? ??? ??????? ???? ?? ??????](#)

????????????[NETUM](#)

?????????

TECHNICAL DATA Light Resource: CCD (Safe visible light)

Port/Interface: USB (standard), RS232 (optional)

Supported Symbolologies: EAN-8, EAN-13, Codabar, CODE11?CODE 39, CODE 93, CODE128, China Post, GS1-128, GS1 Limited, GS1 Omnidirectional, UPC-A, UPC-E, ISBN/ISSN, ISBT , Interleaved 2 of 5?Matrix 2 of 5?Industrial 2 of 5, MSI?Plessey, ITF14

Presicion ?4 mil/0.127mm@PCS90%

Depth of scan field: Code 39:110mm-170mm(0.127mm 5mil) Code 39:100mm-450mm(0.5mm 20mil) Code 39:240mm-480mm(1.0mm 40mil)

UPC/EAN 13:100mm-250mm(0.33mm 13mil)

Battery capacity: 2000MAH

Resolution: 2500

Charging time: 4~6 hours

Decode speed: 300 times/ second

Decode Error Rate: less than 1/8 million

Print Contrast Signal: ?10°

Scan Angle Yaw(Skew): 60° Pitch 60°

Voltage 5VDC ±5%

Current Maximum current :130mA

Operating temperature: 0°C~+50°C

Storage temperature: 20°C~70°C

Humidity: 5%-95%

Applications: Comercial POS system (i.e. supermarkets), Warehousing and logistics, Libraries, Banks and Telecom, Transportaion, Postal service, Industrial and manufacturing management

Packaging:Dims: 165*65*90mm W/O Box / 190mm × 275g - W/Box: 15mm ×85mm; 275g

Weight: 260 gr

?????? ??????
?? ??????? ?????????????? ?? ?? ?????? ??????.